SPECTRA PRECISION®

EPOCH® 35 GNSS SYSTEM

SPECSHEET

GENERAL

When connected to the data collector:

- GPS & GLONASS (GNSS) RTK dual frequency with centimeter accuracy
- Ergonomic, light and compact design
- Integrated Wireless Bluetooth® technology
- Color touch-screen indicators for satellite tracking, data logging
- Application programs, job, and data management
- Access Network RTK with GPRS

TECHNICAL SPECIFICATIONS

Static GNSS surveying[1]

Horizontal . . . . . ±5 mm +0.5 ppm RMS
Vertical . . . . . ±5 mm +1 ppm RMS

Real-Time surveying[1]

Horizontal . . . . . ±10 mm + 1 ppm RMS
Vertical . . . . . ±20 mm + 1 ppm RMS
Initialization . . . . . Automatic OTF (on-the-fly) while moving
Initialization time . . . . . Typically <30 seconds
Start-up . . . . . <60 seconds from power on to positioning
<30 seconds with recent ephemeris

Code differential GPS positioning[1]

WAAS/EGNOS differential positioning accuracy . . . Typically <5 m 3DRMS[2]

Measurements

- Low elevation satellite tracking technology
- 14 L1, 14 L2 GPS, 12 L1, 12 L2 GLONASS, 2 SBAS, WAAS/EGNOS
- NMEA-0183: AVR, GSV, HDT, VGK, VHD, ROT, GGK, GGA, GSA, ZDA, VTG,GST, PJT, and PJK
- 5 Hz position rate

Physical

Dimensions (W×H x D)
GPS receiver . . . . . 19.0 cm x 7.0 cm x 20.0 cm
(7.48 in x 2.76 in x 7.87 in)
Weight
Base . . . . . 1.0 kg (2.2 lb)
Rover . . . . . 1.1 kg (2.4 lb), internal radio, UHF antenna
Ports
I/O . . . . . Two 7-pin Lemo, RS-232
Data Link antenna . . . . . TNC (Rover only)

ENVIRONMENTAL

Operating temperature . . . . . –20 °C to +65 °C (–4 °F to +149 °F)
Storage temperature . . . . . –40 °C to +75 °C (–40 °F to +167 °F)
Humidity . . . . . 95%, condensing
Water/Dust IP64
Shock and vibration: . . . . . Tested and meets the following environmental standards:
Shock . . . . . UNE EN 60068-2-27:1993
Vibration . . . . . MIL-STD-810F Fig 514.5C-1

ELECTRICAL

- Power 10 V DC to 15 V DC external power input with over-voltage protection on Port 1 and Port 2 (7-pin)
- Rechargeable, 7.4v 2400 mAh Li-Ion internal battery
- Power consumption is <2.5 W, in RTK mode with internal radio
  Average operating times on internal battery:
  – RTK/Static: 5.5 hours[3]

COMMUNICATIONS

Base:

- Pacific Crest LPB or HPB positioning data link
- OTA 9600 bps Transparent GMSK
- RTCM 2.1, 2.2, 2.3, 3.0, CMR

Rover:

- Integrated receive-only UHF data link
- RTCM 2.3 & 3.0, CMR, CMR+, NTRIP

NOTICE TO OUR EUROPEAN UNION CUSTOMERS

For product recycling instructions and more information, please go to www.spectraprecision.com/ev.shtml.

Recycling in Europe:
To recycle Spectra Precision WEEE (Waste Electrical and Electronic Equipment products that run on electrical power),
call +31 497 53 24 30, and ask for the "WEEE Associate".
Or, mail a request for recycling instructions to: Spectra Precision,
c/o Menlo Worldwide Logistics, Meerheide 45, 5521 DZ Eersel, NL.

1 Accuracy and reliability may be subject to anomalies such as multipath, obstructions, satellite geometry, and atmospheric conditions. Always follow recommended survey practices.
2 Depends on WAAS/EGNOS system performance.
3 Two batteries supplied standard.

Specifications are subject to change without prior notice.

SPECTRA PRECISION
10355 Westmoor Drive, Suite #100
Westminster, CO 80021
USA
+1-720-587-4700 Phone
888-477-7516 (Toll Free in USA)
www.spectraprecision.com

www.spectraprecision.com
sales@spectraprecision.com
support@spectraprecision.com

© 2008, Spectra Precision. All rights reserved. Spectra Precision and the Spectra Precision logo, and EPOCH are trademarks of Spectra Precision, registered in the United States and in other countries. The Bluetooth word mark and logos are owned by the Bluetooth SIG, Inc. and any use of such marks by Spectra Precision is under license. All other trademarks are the property of their respective owners. PN 022487-144 (01/09)

SPECTRA PRECISION AUTHORIZED DISTRIBUTION PARTNER